




LCD Monitor

| Model | M2BABW | |
|------------------|------------------|---|
| LCD Panel | Type | 22.0" TFT Active Matrix LCD Display |
| | Viewing Angle * | H : 170° , V : 160° * |
| | Contrast Ratio * | 1000 : 1 * |
| | Brightness * | 300 cd/m ² * |
| | Response Time * | 5 ms * |
| | Display Colors * | 16.7M colors * |
| | Max Resolution | 1680 x 1050 (WXGA+) |
| | Pixel Pitch | 0.282mm (H) x 0.282mm (V) |
| Compatibility | PC | Up to 1680 x 1050 @60Hz (Non-interlaced) |
| Connector | RGB Analog | D-sub 15-pins |
| | Audio * | Stereo Phone Jack * |
| | Power | A/C Socket |
| Power | Voltage | 100-240V, 50/60Hz (universal) via internal power supply |
| | Consumption | Active < 54Watt Max |
| Internal Speaker | | Speaker x 2 (Stereo) * |
| Dimensions | Physical | 532mm (W) x 411mm (H) x 173mm (D) |
| Net Weight | | 6Kg ± 1 |
| DDC | | DDC2B Compliant |
| Power Management | | VESA DPMS |
| Others | Security | Kensington Lock Support  |
| Regulation | | CE, FCC, UL |

Notice * LCD Panel and Speakers functions are optional