


# LCD Monitor



## Ambient Light Adaptation (Optional):

Brightness level adjust automatically and continuously base on various different light conditions.



## Product Life Extension:

Optimize and extend product life cycle by enhancing efficiency.

## Visual Ergonomic:

IBT Technology provides comfort and tranquil visual sensation for your eyes.

## Model

## MA9C

LCD Panel	Type	19.0" TFT Active Matrix LCD Display
	Viewing Angle *	H : 140°~160°, V : 130°~150° *
	Contrast Ratio *	500 : 1 ~ 700 : 1 *
	Brightness *	300 ~ 350cd/m <sup>2</sup> *
	Response Time *	8 ~ 12 ms *
	Display Colors *	16.2M ~ 16.7M colors *
	Max Resolution	1280 x 1024 (SXGA)
	Pixel Pitch	0.294mm (H) x 0.294mm (V)
Compatibility	PC	Up to 1280 x 1024 @75Hz (Non-interlaced)
Connector	RGB Analog	D-sub 15-pins
	DVI	DVI-D
	Audio	Stereo Phone Jack
	Power	A/C Socket
Power	Voltage	100-240V, 50/60Hz (universal) via internal power supply
	Consumption	Active < 45Watt Max
Internal Speaker		Speaker x 2 (Stereo)
Dimensions	Physical	433mm (W) x 417mm (H) x 192mm (D)
Net Weight		4.4Kg ± 1
DDC		DDC2B Compliant
Power Management		VESA DPMS
Regulation		CE, FCC, UL

Notice \* LCD Panel functions are optional



Term of list is subject to change without notice.